

MYD-AM335X Development Board

- MYC-AM335X CPU Module as Controller Board
- Two 2.0mm pitch 60-pin Connectors for Board-to-Board Connections
- 720MHz TI AM335X Series ARM Cortex-A8 Processors
- 512MB (2*256MB) DDR3 SDRAM, 512MB Nand Flash
- 2 x Serial ports, 4 x USB2.0 Host, 1 x USB 2.0 OTG, 2 x Gigabit Ethernet, CAN, RS485, TF, Audio
- Supports HDMI and LCD Display
- Optional 4.3 or 7 inch LCD/TSP
- Linux 3.1.0, Android 2.3.4 and Windows Embedded CE 7 BSPs




Figure 1-1 MYD-AM335X Development Board

Description

The MYD-AM335X Development Board designed by MYIR is a high-performance ARM Evaluation Module (EVM) using the MYC-AM335X CPU module as the core controller board. It is based on 720MHz Texas Instruments (TI) Sitara **AM335x** family of ARM Cortex-A8 Microprocessors (MPUs) that deliver high DMIPs at a low cost while also delivering optional 3D graphics acceleration and key peripherals. These TI Cortex-A8 MPUs include industrial interface options, such as EtherCAT and PROFIBUS, and can support the Linux, Android and Windows CE7 high-level operating systems. The combination of graphics and connectivity support makes TI AM335x MPUs ideal for home automation, industrial automation, enterprise/educational tablets, portable navigation devices and networking. The board can work in harsh environment supporting -40 to +85 Celsius extended temperature operation for industrial embedded applications.

The TI AM335x consists of 6 pin-pin compatible devices (AM3352, AM3354, AM3356, AM3357, AM3358 and AM3359) with various options including speed grades, packages, graphics and peripherals. MYIR is using the 15x15 mm, 0.8-mm ball pitch, ZCZ package AM335x ARM CPU on the MYC-AM335X CPU Module which is an SOM (System on Module) and has the core components AM335x processor, 512MB DDR3 SDRAM, 512MB Nand Flash and Gigabit Ethernet PHY chip on board and can be served as the core of your embedded system. It has two 2.0mm pitch 60-pin male expansion connectors, one 2.0mm pitch 26-pin interface and one 2.54mm pitch 10-pin interface to allow extension of all the controller signals and ports to the base board through headers and connectors, thus exposing more features of the AM335x Cortex-A8 Processors.



Figure 1-2 MYC-AM335X CPU Module

The MYD-AM335X base board has extended many features and peripherals with the support of the MYC-AM335X SOM and some extended controller chips including two serial ports, four USB Host ports, one USB OTG port, dual Gigabit Ethernet ports, one CAN, one RS485, one Micro SD, HDMI, LCD, Touch screen and more others.





Figure 1-3 MYD-AM335X Development Board

User can integrate a different MYC-AM335X SOM on the same base board, thus making six variants of AM335x evaluation boards.

- *MYD-AM3359 Development Board* – with *MYC-AM3359 CPU Module* for TI AM3359
- *MYD-AM3358 Development Board* – with *MYC-AM3358 CPU Module* for TI AM3358
- *MYD-AM3357 Development Board* – with *MYC-AM3357 CPU Module* for TI AM3357
- *MYD-AM3356 Development Board* – with *MYC-AM3356 CPU Module* for TI AM3356
- *MYD-AM3354 Development Board* – with *MYC-AM3354 CPU Module* for TI AM3354
- *MYD-AM3352 Development Board* – with *MYC-AM3352 CPU Module* for TI AM3352



✓ PRU-ICSS is used for slave industrial communication protocols such as Profibus, Profinet, Powerlink & Ethernet/IP

Package	15x15mm (ZCZ)
ARM speed	Up to 1000 MHz
USB 2.0 OTG + PHY	x2
EMAC	2-port switch

Figure 1-4 AM335x Devices Comparison

The MYD-AM335X series ARM Cortex-A8 boards have many features in common only with some differences depending on the AM335x Cortex-A8 CPU features. You can get to know the differences from above image (see Figure 1-4). MYIR delivers the MYD-AM3352 and MYD-AM3359 by default according to customer's specified model. Other four models are only available for mass quantity demand.

The MYD-AM335X board comes with Linux 3.1.0, Android 2.3.4 and Windows CE7 software packages, detailed documents, necessary cable accessories as well as optional 4.3- and 7-inch LCD (with touch screen) to provide an AM335x starter kit and enable a quickly start of evaluation of AM335x Cortex-A8 MPUs.

The MYD-AM335X Development Kit includes following items:



MYD-SAMA5D3X board



Ethernet cable



USB cable



5V Power Adapter



Product DVD



Optional 4.3- or 7-inch LCD/TSP

Figure 1-5 MYD-AM335X Development Kit

Hardware Specification

The [TIAM335x](#) microprocessors, based on the ARM Cortex-A8, operating at up to 1GHz, are enhanced with image, graphics processing, peripherals and industrial interface options such as EtherCAT and PROFIBUS. The device supports the following high-level operating systems (HLOSs) that are available free of charge from TI:

- Linux®
- Android™

The AM335x microprocessor contains these subsystems:

- Microprocessor unit (MPU) subsystem based on the ARM Cortex-A8 microprocessor.
- POWERVR SGX™ Graphics Accelerator subsystem for 3D graphics acceleration to support display and gaming effects.
- The Programmable Real-Time Unit and Industrial Communication Subsystem (PRU-ICSS) is separate from the ARM core, allowing independent operation and clocking for greater efficiency and flexibility. The PRU-ICSS enables additional peripheral interfaces and real-time protocols such as EtherCAT, PROFINET, EtherNet/IP, PROFIBUS, Ethernet Powerlink, Sercos, and others.

AM335x ARM Cortex™-A8 Processors						
Core Feature	AM3352	AM3354	AM3356	AM3357	AM3358	AM3359
Package	15x15mm, 0.8mm (ZCZ)					
CPU Speed (MHz)	300, 600, 800, 1000	600, 800, 1000	300, 600, 800	300, 600, 800	600, 800, 1000	800
Core Internal Memory	64KB SRAM shared w/ Data 32KB Cache, Programmable 32KB Cache					
On-chip L2 (KB)	256					
External Memory Interface	DDR2/DDR3/DDR3L/mDDR (LPDDR), 2x16-bit, NAND ECC					
Graphics	-	3D Graphics	-	-	3D Graphics	
OS Support	Linux, Android, RTOS, Windows Embedded, no-OS					
Other Hardware Acceleration	Crypto Accelerator	Crypto Accelerator	2 PRU-ICSS Crypto Accelerator	2 PRU-ICSS Crypto Accelerator + EtherCAT slave support	2 PRU-ICSS Crypto Accelerator	2 PRU-ICSS Crypto Accelerator + EtherCAT slave support
10/100/1000 EMAC	2 port switch					
USB 2.0 OTG + PHY	2					
Serial Ports	6 UART, 2 SPI, 3 I2C, 2 McASP, 2 CAN, 8 Timers					
System	EDMA, WDT, RTC, 3 eQEP, 3 eCAP, JTAG, ADC (8ch)					
Parallel	3 MMC/SD/SDIO, GPIO					

Table 1-1 AM335x Devices Key Features

The MYD-AM335X has a CPU Module MYC-AM335X integrated with AM335x processor, DDR3 SDRAM, Nand Flash and Gigabit Ethernet PHY on it, which exposes many of these features to the user in support of developing specific solutions. The CPU Module can be mounted directly onto the base board through two 2.0mm pitch 60-pin expansion connectors. This board is characterized as follows:

Mechanical Parameters

- Dimensions: 130mm x 100mm (base board), 70mm x 50mm (CPU Module)
- PCB Layers: 4-layer design (base board), 6-layer design (CPU Module)
- Power supply: +5V/2A (base board), +3.3V/0.8A (CPU Module)
- Working temperature: 0~70 Celsius (commercial grade) or -40~85 Celsius (industrial grade)

Note: Our products are delivered of commercial grade (0~70 Celsius) by default. Anyhow the MYD-AM335X boards based on TI AM335x ARM Cortex-A8 processors can work for industrial applications working in harsh environment with working temperature ranging from -40 Celsius to 85 Celsius. Please contact MYiR for price and availability of products of industrial grade if you needed.

The MYD-AM335X Controller Board (MYC-AM335X CPU Module)




Figure 1-6 MYC-AM335X Top-view




Figure 1-7 MYC-AM335X Bottom-view

Processor

- TI AM3352, AM3354, AM3356, AM3357, AM3358, AM3359 (15x15 mm, 0.8-mm ball pitch, ZCZ package)
 - 720-MHz ARM Cortex-A8 32-bit RISC MPU (Up to 1GHz)
 - NEON™ SIMD Coprocessor
 - 32KB/32KB of L1 Instruction/Data Cache with Single-Error Detection (parity)
 - 256KB of L2 Cache with Error Correcting Code (ECC)
 - SGX530 Graphics Engine
 - Programmable Real-Time Unit Subsystem

Memory

- 512MB DDR3 SDRAM
- 512MB Nand Flash

Peripherals and Signals Routed to Pins

- On-board Gigabit Ethernet PHY
- One power indicator (Red LED)

- One user LED (Green)
- Two 2.0mm pitch 60-pin expansion connectors can carry out interfaces below
 - 2 x USB2.0 OTG ports
 - 6 x Serial ports
 - 2 x I2C
 - 1 x SPI
 - 7 x ADC
 - 2 x PWM
 - 3 x SDIO
- One 2.0mm pitch 26-pin expansion interface
- One 2.54mm pitch 10-pin expansion interface

The MYD-AM335X Base Board




Figure 1-8 MYD-AM335X Base Board

- Serial ports
 - 1 x 3-wire RS232 Debug serial port (DB9)
 - 1 x 3-wire RS232 serial port (UART1)
 - 1 x RS485 (with isolation)
- USB
 - 4 x USB2.0 Host ports
 - 1 x USB2.0 OTG ports
- 2 x 10/100/1000Mbps Ethernet interfaces
- 1 x CAN interface (with isolation)
- 1 x TF card slot
- 1 x HDMI interface
- 1 x LCD interface (16-bit true color, supports optional 4.3-inch and 7-inch TFT LCD)
- 1 x 4-wire resistive touch screen interface
- 1 x Audio input port (3.5mm jack)
- 1 x Stereo Audio output port (3.5mm jack)
- 4 x Buttons (1 x Reset button, 3 x User buttons)

- 1 x Power indicator (Red LED)
- 2 x 2.0mm 20-pin expansion connectors
 - 7 x ADC
 - 1 x SPI
 - 2 x I2C
 - 4 x UART

Function Block Diagram




Figure 1-9 Function Block Diagram of MYD-AM335X

Dimension Chart of MYD-AM335X




Figure 1-10 Dimension Chart of MYD-AM335X

Software Features

MYiR's AM335x Starter Kit MYD-AM335X supports for Linux, Android and WinCE and is provided with software packages. Many peripheral drivers are in source code to help accelerate customers' designs with a stable and reliable hardware and software platform. The software features are summarized as below:

OS	Item	Features	Description
Linux	Bootstrap program	SPI	The primary bootstrap
		u-boot	The secondary bootstrap
	Kernel	Version	Linux 3.1.0
	Drivers	USB OTG, USB WiFi, Gigabit Ethernet, MMC/SD/TF, NandFlash, CAN, RS485, Audio, LCD Controller (supports 4.3- and 7-inch LCD), RTC, HDMI, Touch driver, Button, UART, LED	
	File system	UBIFS	Provide image file
Android	Bootstrap program	Bootstrap	Used for u-boot
		u-boot	The secondary bootstrap
	Kernel	Version	Linux 3.1.0
	Drivers	USB OTG, Ethernet, SD, Audio, LCD Controller (supports 4.3- and 7-inch LCD), RTC, HDMI, Touch driver, Button	
	File system	Android 2.3.4 file system	Provide binary image file
WinCE	Bootstrap program	X-loader	The primary bootstrap
		e-boot	The secondary bootstrap
	Kernel	Version	Windows Embedded Compact 7
	Drivers	USB OTG, Gigabit Ethernet, GPIO, MMC/SD/TF, NandFlash, I2C, SPI, MCASP, Audio, LCD Controller (supports 4.3- and 7-inch LCD), Touch driver, Backlight, Battery, RPU, UART, GPIO Keyboard, DMA, LED	
	File system	BINFS	Provide binary image file

Order Information

Product Item	Part No.	Packing List
MYD-AM3352 Development Board	MYD-AM3352	<ul style="list-style-type: none"> ➤ One MYD-AM335X Development Board ➤ One Net cable ➤ One USB cable ➤ One 5V/2A Power adapter ➤ One Product DVD (including user manual, datasheet, schematic in PDF format and software packages)
MYD-AM3359 Development Board	MYD-AM3359	
MY-LCD43TP 4.3-inch LCD Module	MY-LCD43TP	
MY-LCD70TP 7-inch LCD Module	MY-LCD70TP	
MYC-AM3352 CPU Module	MYC-AM3352	
MYC-AM3359 CPU Module	MYC-AM3359	

Add-on Options

- MY-LCD43TP 4.3-inch LCD Module
- MY-LCD70TP 7-inch LCD Module
- MYC-AM335X CPU Module

Remark:

1. One MYD-AM335X Development Board includes one CPU module MYC-AM335X mounted on the base board. If you need more CPU module, you can order extra ones.
2. MYIR offers MYD-AM3352 and MYD-AM3359 by default; other four models (MYD-AM3354, MYD-AM3356, MYD-AM3357 and MYD-AM3358) are only available for mass quantity demand.
3. For Price information, please contact MYIR.
4. Our products are delivered of commercial grade (0~70 Celsius) by default. Anyhow the MYD-AM335X boards based on TI AM335x ARM Cortex-A8 processors can work in harsh environment with working temperature ranging from -40 to 85 Celsius. Please contact us for price and availability of products of industrial grade if you needed.
5. We accept custom design based on the MYD-AM335X, whether reducing, adding or modifying the existing hardware according to customer's requirement.


MYIR Tech Limited

Room 1306, Wensheng Center, Wenjin Plaza, North Wenjin Road, Luohu District, Shenzhen, China 518020

E-mail: sales@myirtech.com

Phone: +86-755-22984836

Fax: +86-755-25532724

Website: <http://www.myirtech.com>